

PATENT SPECIFICATION

Convention Date (United States): Feb. 15, 1936.

490,433

Application Date (in United Kingdom): Feb. 15, 1937. No. 4498/37.

Complete Specification Accepted: Aug. 15, 1938.



COMPLETE SPECIFICATION

Improvements in Processes of High Vacuum-short Path Distillation

We, EASTMAN KODAK COMPANY, a Company organised under the laws of the State of New Jersey, United States of America, of 843, State Street, Rochester, 5 State of New York, United States of America (Assignees of KENNETH CLAUDE DEVEREUX HICKMAN, a British subject, of Kodak Park, Rochester, County Monroe, State of New York, United 10 States of America), do hereby declare the nature of this invention and in what manner the same is to be performed, to be particularly described and ascertained in and by the following statement:—

15 This invention relates to improvements in processes of high vacuum-short path distillation, particularly that specific form of high vacuum-short path distillation in which the distance separating 20 evaporating and condensing surfaces is equal to or less than the mean free path of the molecules of the distilland, herein referred to as molecular distillation.

Processes of high vacuum-short path distillation are well known and have been 25 applied to the distillation and purification of various materials. Thus, Burch U.S. Patent Specification 1,955,821 discloses the molecular distillation of hydrocarbon oils and in U.S. Patents specifications 1,925,559 and 1,942,858 Hickman 30 has disclosed the similar distillation of vegetable and animal oils, fats, and waxes in order to concentrate therapeutic agents contained therein. Process of high vacuum-short path distillation have been applied to the treatment of numerous other types of materials such 40 as sterols, hormones, etc. and materials containing same. The materials so treated are often of a viscous character, of high molecular weight and therefore do not flow with sufficient rapidity through the still. This results in over- 45 heating and decomposition of valuable constituents and is especially disastrous when materials containing heat sensitive substances such as vitamins are treated. Often the materials to be distilled contain 50 dissolved substances which are thrown out of solution on distillation of part of the solvent and this material deposits on the heated evaporating surface where it

continues to collect resulting in clogging 55 of the apparatus. Where the constituents of the mixture to be distilled boil at nearly the same temperature the entire liquid may evaporate leaving a deposit of non-volatile residue on the evaporating surface. As the evaporating and condensing 80 surfaces are arranged in close proximity the deposit cannot be effectively removed unless the whole still is dismantled which involves considerable loss in time and expense. A clean 85 evaporating surface is important for efficient distillation, and it has been necessary until the advent of this invention to periodically dismantle the still and mechanically remove deposited 70 materials.

This invention has for its object to overcome the deficiencies of hitherto known high vacuum-short path distillation processes by providing a process in 75 which viscous material or materials yielding vitamins, sterols, hormones or unsaturated glycerides and tending to deposit solid substances can be distilled without clogging of the distillation 80 apparatus and without decomposition of heat sensitive materials contained therein. A remedy is also sought for preventing deposition of non-volatile substances in high vacuum-short path distillation processes when the constituents 85 of the mixtures being distilled have closely allied boiling points.

According to the present invention, substances which are liquid at the temperature of the still and which on distillation yield vitamins, sterols, hormones or unsaturated glycerides, are subjected 90 to high vacuum-short path distillation, there being added to the original distilland or a fraction thereof still requiring distillation, another liquid having a vapour pressure lower than that of the distillate under the conditions appertaining, thereby preventing deposition of 100 non-volatile residuum upon the distilling surface tending to clog the still.

It has already been proposed to subject finely-divided solid materials to molecular distillation by mixing them with a 105 liquid serving as a vehicle or carrier, e.g.

[Price 1/-]

the high vacuum-short path distillation of solid placenta, dispersed in an oil, so as to yield a fraction containing the female sex hormone, has already been proposed but in our process the liquid diluent is added to a distilland which is itself liquid at the temperature of the still, for the purpose of accelerating the flow of the liquid over the distilling surface, for example, by lowering the viscosity or surface tension of the distilland.

In the following examples and description several of the preferred embodiments of the invention are set forth, but it is to be understood that they are included merely for purposes of illustration and not as a limitation thereof.

For achieving the best results by means of the present invention a liquid should be selected which is miscible with the distilland, since the precipitation of solids will be more effectively prevented. However, non-miscible or partially miscible liquids may be used since they dissolve precipitated solids or will mechanically entrain and remove precipitated solids which are not soluble therein. The selection of the liquid agent obviously depends upon the character of the particular distilland and the vapour pressure of the distillate to be removed. Where the distillate has a relatively low vapour pressure the liquid need not have an excessively low volatility. It is important, however, to select a liquid which has a lower vapour pressure than the distillate or it will also distil giving no beneficial results as far as the removal of solids is concerned. Preferably a liquid is employed which also has a considerably lower vapour pressure than the distilland especially where contamination of the distillate by the entraining agent is undesirable.

In speaking of substances having a relatively high or low volatility it is to be understood that this invention relates to high vacuum-short path distillation and in such processes materials generally recognized as being of low volatility are usually distilled and the comparison is therefore between substances which are considered to be relatively non-volatile under conditions of normal temperature and pressure but which may have appreciable and comparable volatilities when subjected to the high temperature and low pressures associated with high vacuum-short path distillation. Thus, in distilling a substance such as propylene glycol which has a relatively high volatility in the field of high vacuum distillation, a liquid having a lower vapour pressure such as triphenyl phosphate may be

employed to prevent deposition. The phosphate has a vapour pressure which is also rather high but is sufficiently low to enable distillation of the glycol without substantial contamination. In distilling those natural vegetable and animal oils which serve as sources of vitamins, sterols, hormones, or unsaturated glycerides, substantially no residue is left to carry away dissolved solids and protein matter. As such oils consisting substantially of glycerides have a low volatility it is necessary to add a liquid agent which has a very low vapour pressure. The particular agent selected depends upon the nature of the glyceride or oil to be treated and where the glyceride to be distilled is of rather high volatility as compared with other glycerides the latter may be used as the liquid agents. Thus, in distilling linseed, salmon or cottonseed oil, a glyceride of very low volatility such as castor oil may be added.

Instead of using a foreign liquid it is often convenient to use the lowest vapour pressure fraction of the oil which is to be distilled. Most unsaturated natural oils contain a small quantity of extremely non-volatile liquid residue. If this residue passes too slowly over the heated surface of the still it may dry down in spite of its low volatility or it may decompose or polymerize. By increasing the rate of travel through the still especially at the hottest portions this non-volatile residue mixed with constituents which it is desired to volatilize can be easily withdrawn and partially or entirely returned to some previous position or stage of the still. It may thus be added to the original oil to be distilled or to the hot columns which it is desired to lubricate. In this way any desired proportion of non-volatile liquid may be accumulated and recirculated.

The proportions of liquid agent used are not critical and may be several times the weight of the distilland or only a fraction thereof depending upon the physical characteristics of the material to be distilled, the amount of solids dissolved therein and their tendency to precipitate, and upon the amount of the distilland which is to be removed as distillate, tendency to polymerize etc. Where the distilland is viscous and contains a high proportion of dissolved solid or gelatinous material, a higher proportion must be used such as equal proportions, or in some cases 2, 5 or as high as 25 parts or more of liquid to 1 of distilland. The same is true where substantially all of the liquid portion of the distilland is to be removed as distillate.

In molecular distillation processes a low pressure usually less than .1 mm. is employed, resulting in an appreciable mean free path. Pressures of less than about .01 mm. such as for instance, about 180

.001 mm. to .0001 mm. are preferred. However, as the mean free path is inversely proportional to the pressure it is apparent that the higher the degree of vacuum, the greater will be the rate of distillation. It is therefore possible to use evaporating and condensing surfaces situated within one inch at a residual operating pressure of less than 3 microns mercury or within a quarter of an inch at less than 8 microns mercury, or within 10 inches at less than .3 microns mercury and so forth. With pressure and distance as interchangeable quantities in molecular distillation no real lower limit to the pressure or upper limit to the distance can be defined, but for reasons of expediency it is preferable not to operate with a residual gas pressure of less than .01 microns mercury or a distance of greater than 10 ft. Distances of less than about 10 inches such as $\frac{1}{2}$ inch to 6 inches have been found to be most suitable.

In selecting the temperatures to be used in high vacuum short path and especially molecular distillation processes consideration must be given to the character of the material to be distilled and of pressures used. Materials of very low volatility must be heated to temperatures approaching their decomposition point even though the lowest pressures attainable are employed. With such compounds temperatures as high as 325° C. are useful. On the other hand the separation of easily volatilizable compounds can be effected at low temperatures such as at room temperatures or slightly higher such as up to about 70° C. Most materials have vapour pressures intermediate between these two extreme types and they may be satisfactorily distilled at temperatures of 70° to 300° C. and usually at lower temperatures of between 70° and 250° C. The latter range and especially those temperatures between 90° and 230° C. have been found to be most satisfactory for the distillation of vitamins from vitamin containing oils.

While the invention has been described as being especially applicable to processes of molecular distillation it is applicable to all processes of high vacuum-short path distillation where a troublesome problem in circulation of a distilland of the kind as hereinbefore defined and clogging of apparatus is encountered. It is, however, especially useful in processes of molecular distillation since the evaporating surfaces are necessarily very large and it is important to distribute the distilland thereon in a thin layer.

The materials used as diluents of the distilland may be any organic compounds or mixtures thereof which have the requisite physical properties as regards vapour pressure, and viscosity. Thus glycerides such as castor oil, and olein, phthalates such as benzyl, butyl, amyl, and octyl phthalate, high boiling alcohols such as mono, di and tri glycerol, esters such as triacetin, methyl oleate, and stearate, high boiling hydrocarbons such as lubricating oil, "Apieson" oils, etc., may be employed. Obviously no liquid should be selected which has a high viscosity or decomposes at the temperature at which it is employed.

As already stated the process of the invention is applicable to the high vacuum-short path distillation of any substances containing vitamins, sterols, hormones or unsaturated glycerides which have a high viscosity or tendency to deposit solids on the evaporating surface. Examples of materials to which the invention has been applied, in addition to those given above are the distillation of crude animal and vegetable oils, fats and waxes as hereinbefore defined, such as linseed, walnut, soya menhaden, cottonseed, wheat germ, salmon, cod-liver, herring, halibut, mackerel, etc., to recover unsaturated glycerides and/or therapeutic agents such as fat soluble vitamins and sterols; crude germinal gland hormone concentrates and synthetic reaction mixtures containing them.

It is to be understood that the term liquid agent designates materials which are liquid under normal conditions as well as those materials which are viscous liquids or solids under normal conditions but which readily flow at the temperature of the still.

The herein described process affords an economical simple and effective solution of the vexatious problem of preventing deposited solids from clogging or lowering the efficiency of a high vacuum-short path still. By means of the invention viscous and deposit-forming materials may be rapidly run through a molecular still and evenly spread in a thin layer over the evaporating surface without thermal decomposition or deposition of solids.

Having now particularly described and ascertained the nature of our said invention and in what manner the same is to be performed, we declare that what we claim is:—

1. The process of short path-high vacuum distillation of substances which are liquid at the temperature of the still and which on distillation yield fractions containing vitamins, sterols, hormones or unsaturated glycerides, in which there is added to the original distilland or a fraction obtained therefrom still requiring

distillation another liquid having a vapour pressure lower than that of the distillate under the conditions appertaining, thereby preventing deposition of non-volatile residuum upon the distilling surface, tending to clog the still.

2. The process as claimed in claim 1 applied specifically to substances which are normally liquids.

3. The process as claimed in claim 1 or 2 carried out under conditions of molecular distillation.

4. The process as claimed in claim 1, 2 or 3 in which the distilland diluent is separated from the distilland remaining after distillation and then recycled.

5. The process as claimed in claim 4 in which a distilland diluent is used

which is miscible with the distilland when hot, but immiscible when cold. 20

6. The process as claimed in claim 1, 2 or 3 in which a non-volatile liquid fraction of the original distilland is recirculated, at least in part, to serve as the distilland diluent. 25

7. The process as claimed in claims 1, 2 or 3 in which the original distilland diluent comprises a mixture of a liquid having a vapour pressure lower than that of the distillate and a non-volatile liquid distilland fraction remaining from a previous "run". 30

Dated this 12th day of February, 1937

W. P. THOMPSON & Co.,
12, Church Street, Liverpool,
Chartered Patent Agents.